

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



536 724

(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/007331 A1

(51) International Patent Classification⁷: B23D 79/02

(21) International Application Number:
PCT/IT2004/000304

(22) International Filing Date: 26 May 2004 (26.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
MO2003A000208 22 July 2003 (22.07.2003) IT

(71) Applicant (for all designated States except US): OTO
MILLS, S.P.A. [IT/IT]; Via Domenico Marchesi, 4, Zona
Industriale Rondello, I-42022 Boretto (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MICALI, Luciano
[IT/IT]; Viale Cappuccini, 14/2, I-42016 Guastalla (IT).

(74) Agent: GIANELLI, Alberto; Bugnion S.p.A., N°25, Via
Emilia Est, I-41100 Modena (IT).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: AN EXTERNAL BEAD TRIMMER WITH A SHAVING BREAKER DEVICE



(57) Abstract: The bead-trimmer with a
shaving breaker device comprises a support
(2) having at an end thereof a through-hole
(3) which bears, on an entrance edge thereof a
cutting element (4) arranged and conformed to
remove, during a cutting motion, an external
weld bead (20) and to direct a resulting
shaving (21) through the through-hole (3), the
through-hole (3) bearing, in proximity of an
exit edge thereof, means for chopping (5) the
shaving, predisposed to fragment the shaving
coming from the through-hole (3).

WO 2005/007331 A1

Description

An External Bead Trimmer with a Shaving Breaker Device.

Technical Field

The invention belongs to the field of bead trimmers, and includes a breaker device for the bead shavings.

Background Art

The prior art includes external bead trimmers in machines predisposed on continuous production lines for elements which are longitudinally welded. These machines, equipped with a trimming tool, remove from the outside surface of the elements excess bead from the longitudinal weld seam. The tool is placed in contact with the weld bead of the elements, which run longitudinally and continuously. The bead is removed continuously from the elements, with the bead becoming a shaving which flows more or less continuously, depending on the material being treated and the cutting parameters; whence it forms hanks of shaved beads.

The hanks are generally taken to a pressing system or a chopping group in the vicinity of the machine. Alternatively, in some cases, the shaving are removed and wound up to form an ordered hank.

The prior art exhibits some drawbacks. The variability of the flow of shaving and the tendency the shavings have to coil up into a shapeless hank necessitate the constant presence of an operative who, using special metal hooks, drives the material towards the pressing system. If the shavings are wound continuously into an ordered hank, when the bead breaks, as is frequent, the operative must hook up the lengths of shaving to the hank so that the continuity is not lost. In

-2-

both cases the operative is working in conditions of a certain level of risk inasmuch as the shavings are sharp and rather hot, i.e. at a temperature of not less than 300°C. The operative's presence is also necessary for removing the pressed hank.

5 The main aim of the present invention is to obviate the drawbacks in the prior art. An advantage of the present invention is that it enables a completely automatic management of the shavings coming from the bead trimmer.

A further advantage of the invention is that the treated shavings have a simple and easy shape to manage, so the manual operations required are minimal.

10 A further advantage of the invention is that it is perfectly suited to high-speed production cycles.

Disclosure of Invention

Further characteristics and advantages of the present invention will better emerge from the detailed description that follows of a preferred but non-exclusive
15 embodiment of a bead trimming machine with a shaving breaker device, illustrated purely by way of a non-limiting example in the accompanying figures of the drawings, in which:

figure 1 is a schematic view in section of the tool of the invention in a first work stage;

20 figure 2 is the tool of figure 1 during a second work stage;

figure 3 is the tool of figure 1 during a third work stage;

figure 4 is the tool of figure 1 in a fourth work stage.

With reference to the figures of the drawings, 1 denotes in its entirety the tool of the present invention. It comprises a support 2 having at one end thereof a
25 through-hole 3 which on an entrance edge 3a thereof bears a cutting element 4 arranged and conformed so as to remove, during a cutting motion, an external weld bead 20 and direct the resulting shaving 21 through the through-hole 3. The

-3-

cutting motion is performed along a direction x which is parallel to the longitudinal axis of an element which longitudinally exhibits the external weld bead 20. In the illustrated embodiment, the support 2 is stationary while the element 19 is made to slide longitudinally. The support 2 exhibits a front surface 2a on which the edge of the entrance of the through-hole 3 is situated, and a rear surface 2b, on which an exit edge of the through-hole 3 is situated. As can be seen in the accompanying figures of the drawings, the support 2 is arranged so that the longitudinal axis y of the through-hole 3 forms a predetermined angle with respect to the direction x along which the cutting motion takes place. The cutting element 4 removes the bead 20 at a predetermined cutting angle and the removed shaving flows along the through-hole 3 up until it exits from the exit edge 3b.

Means 5 for chopping the shavings are provided in proximity of the exit edge 3b of the through hole 3, which means 5 for chopping fragment the shavings exiting from the through-hole 3. The means for chopping 5 comprise a blade 6 which exhibits a first cutting edge 6a and a second cutting edge 6b which is opposite the first cutting edge 6a. The blade 6 is slidable, during the cutting motion, on a surface containing the exit edge 3b of the through-hole 3 in an alternating motion. In the illustrated embodiment the blade 6 runs on the rear surface 2b of the support 2. During the alternating motion the blade 6 transits on the section of the through-hole 3, shuttling between a first "dead" point and a second dead point, arranged on opposite sides with respect to the through-hole 3, at which dead points the blade 6 is external of the exit edge 3b of the through-hole. The blade 6, in its alternating sliding motion, slides to and fro over the area of the exit section of the through-hole.

The alternating motion of the blade 6 happens contemporaneously with the cutting motion. Assuming as a start point of the blade 6 the first dead point and

-4-

considering a work run of the bead trimming of the bead to be constituted by the interval of time from when the first cutting edge 6a moves from the position assumed at the first dead point to when the first cutting edge 6a is in a position in which it completes its transit over the exit of the through-hole 3, the shaving

5 21 increases in length by an amount which is about equal to the product between the bead cutting speed and interval of time considered. By regulating the two operative parameters the shaving 21 can be made to project from the exit edge 3b of the through-hole 3 by a predetermined length. Thus, in the motion of the blade

10 6 from the first dead point to the second dead point at least a section of shaving 21, which is in movement through the through-hole 3, is caught between the first cutting edge 6a and at least a tract of the exit edge 3b of the through-hole 3, the shaving thus being cut at this section. The blade 6 concludes its run at the second dead point, at which it is external to the exit edge 3b of the through-hole 3.

15 Similarly, in the motion of the blade 6 from the second dead point to the first dead point, during the time interval in which the second cutting edge 6b moves from the second dead point to the position at which it has completed its transit over the exit section of the through-hole 3, the shaving 21 increases in length by a measurement equal to about the product between the speed of cut of the bead

20 20 and the time interval considered. During this "return" run of the blade 6, at least a section of the shaving 21, which is still moving through the through-hole 3, is caught between the second cutting edge 6b and the exit edge of the through-hole 3 and is cut.

25 In the illustrated embodiment, the through-hole 3 is circular in section and the dead points of the alternating motion of the blade 6 are diametrically opposite with respect to the through-hole 3. The axes x, y and the sliding direction of the blade 6 are coplanar and lie on a vertical plane. As can be seen in figures 2 and 4, the shaving 21 is cut at the diameter points of the exit edge 3b lying along the

sliding direction of the blade 6. The blade 6 is associated to a support 6c, slidable on the rear surface 2b of the support 2, by two arms connected at ends thereof in such a way as to take the form of a guillotine. The two connection arms are of such a length and at such a distance so that the support 6c does not interfere with the through-hole 3.

By regulating the sliding speed of the blade 6 and the cutting speed of the bead 20, the length of the lengths of cut shaving 21 can be set to adapt them to the system of removal and disposal used on the production line.

The invention offers important advantages. Firstly, the shaving is reduced to a form which greatly simplifies its treatment and management. As it is chopped up into lengths, it can be collected in containers arranged in proximity of the bead-trimming machine and be removed therefrom automatically. The presence of an operative is thus needed only for control purposes, thus avoiding the particularly high risks connected with the manipulation of a dangerous shaving, which is very hot and might cut. The invention can also be adapted to suit any type of material and any set of working parameters, simply by regulating the frequency of the blade run.

Claims.

- 1). An external bead trimmer with a shaving breaker device, wherein it comprises a support (2) having at an end thereof a through-hole (3) which bears, on an entrance edge thereof, a cutting element (4) arranged and conformed to remove, during a cutting motion, an external weld bead (20) and to direct a resulting shaving (21) through the through-hole (3), the through-hole (3) bearing, in proximity of an exit edge thereof, means for chopping (5) the shaving, predisposed to fragment the shaving coming from the through-hole (3).
- 2). The tool of claim 1, wherein the means for chopping (5) for fragmenting the shaving comprise a blade (6) having a first cutting edge (6a) and a second cutting edge (6b) opposite the first cutting edge (6a), the blade (6) being slidable, during a cutting motion, on a surface containing the exit edge of the through-hole (3) with an alternating motion in which the blade (6) transits over a section of the through-hole (3), moving between a first dead point and second dead point at which first and second dead points it is external of the through-hole (3).
- 3). The tool of claim 2, wherein in the motion of the blade (6) from the first dead point to the second dead point, at least a section of the shaving (21), which shaving (21) is moving through the through-hole (3), is caught between the first cutting edge (6a) and at least a tract of the exit edge of the through-hole (3), so that the shaving (21) is cut at the section thereof.
- 4). The tool of claim 2, wherein in the motion of the blade (6) from the second dead point to the first dead point at least a section of shaving (21), which is moving through the through-hole (3), is caught between the second cutting edge (6b) and at least a tract of the exit edge of the through-hole (3), so that the shaving (21) is cut at the section thereof.

-7-

5). The tool of claim 1, wherein the support (2) exhibits a front surface (2a) on which the entrance edge of the through-hole (3) is located, and a rear surface (2b) on which the exit edge of the through-hole (3) is located and on which the blade (6) runs.

5 6). The tool of claim 1 or 2, wherein the through-hole (3) is circular in section and the dead points of the alternating motion of the blade (6) are diametrically opposite with respect to the through-hole (3).

7). The tool of claim 2, wherein the blade (6) is associated to a support (6c) which is slidable on the rear surface (2b) of the support (2), by means of two
10 arms connected at ends thereof, the arms being of a length and being arranged at a reciprocal distance from one another such that the support (6c) does not interfere with the through-hole (3).

Fig. 2




Fig. 4




Fig. 1





Fig. 3



INTERNATIONAL SEARCH REPORT

In Application No
PCT/IT2004/000304

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B23D79/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B23D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 91/01839 A (BARRACLOUGH KEITH SYLVESTER ; CAREY IAN (GB)) 21 February 1991 (1991-02-21) figures 5,6	1-7
A	EP 0 150 414 A (ARBED TECHNO GMBH) 7 August 1985 (1985-08-07) figure 6	1-7
A	US 5 275 470 A (MILLER CHARLES E) 4 January 1994 (1994-01-04) page 4	1-7



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

2 September 2004

Date of mailing of the international search report

10/09/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5618 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Florani, G

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. Application No
PCT/IT2004/000304

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9101839	A	21-02-1991	WO 9101839 A1	21-02-1991
EP 0150414	A	07-08-1985	DE 3347146 C1	14-03-1985
			AT 29228 T	15-09-1987
			DE 3465713 D1	08-10-1987
			EP 0150414 A1	07-08-1985
			JP 1517471 C	07-09-1989
			JP 60155309 A	15-08-1985
			JP 63065449 B	15-12-1988
			US 4710078 A	01-12-1987
US 5275470	A	04-01-1994	NONE	